

Menu Route Map

Preferences

- Sound Volume Control**
 - Fax Tone**
 - Off
 - On**
 - Fax Volume: **1** to 5
 - Ring Tone**
 - Off
 - On**
 - Ring Tone Volume: **1** to 5
 - TX Done Tone**
 - Off
 - On**
 - TX Done Volume: **1** to 5
 - Sound Only When Error Occurs
 - TX Done Volume: **1** to 5
 - RX Done Tone**
 - Off
 - On**
 - RX Done Volume: **1** to 5
 - Sound Only When Error Occurs
 - RX Done Volume: **1** to 5
 - Scanning Done Tone**
 - Off
 - On**
 - Scanning Done Volume: **1** to 5
 - Sound Only When Error Occurs
 - Scanning Done Volume: **1** to 5
 - Entry Tone**
 - Off
 - On**
 - Entry Tone Volume: **1** to 5
 - Entry Error Tone**
 - Off
 - On**
 - Entry Err. Tone Volume: **1** to 5
 - Warning Tone**
 - Off
 - On**
 - Warning Tone Volume: **1** to 5
 - Job Done Tone**
 - Off
 - On**
 - Job Done Tone Volume: **1** to 5
 - Handset Volume**
 - High, **Low**
- Display Settings**
 - Language**
 - English**
 - French
 - Portuguese
 - Spanish
 - Contrast**
 - 2 to **0** to +2
 - Invert Screen Colors**
 - Off**, On
 - mm/Inch Entry Switch**
 - mm, **Inch**
 - Gram/Pound Switch**
 - Gram, **Pound**
 - Message Display Time**
 - 1 to **2** to 5 (seconds)
 - Scrolling Speed**
 - Slow, **Normal**, Fast
 - Cursor Movement**
 - Auto**, Manual
- Toner Saver Mode**
 - Copy**
 - Off**, On
 - Fax**
 - Off**, On

Copy Settings

- Change Defaults**
- Correct Density**
 - 4 to **0** to +4

Fax TX Settings

- Basic Settings**
 - Register Unit Name**
 - Register Unit Telephone Number**
 - Select Line Type**
 - Pulse, **Tone**
 - Public Line Connection**
 - Direct**, Adapter 1, Adapter 2
 - Off-Hook Alarm**
 - Off**
 - On
 - Off-Hook Alarm Volume: **1** to 5
 - Sender ID**
 - Off
 - On**
 - Print Location: On Image, **Above Image**
 - Mark No. as: TEL/FAX: **FAX**, TEL
- TX Function Settings**
 - Change Defaults**
 - ECM TX**
 - Off, **On**
 - Pause Time**
 - 1 to **2** to 15 (seconds)
 - Auto Redial**
 - Off
 - On**
 - Redial Times: 1 to **2** to 10 (times)
 - Redial Interval : **2** to 99 (minutes)
 - Redial When Err Occurs: Off, **On**
 - Check Dial Tone Before Sending**
 - Off**, On
- Fax Setup Guide**

Fax RX Settings

- RX Function Settings**
 - Reduce RX Size**
 - Off
 - On**
 - Reduction Ratio: **Auto**, 97, 95, 90, 75 (%)
 - Reduction Direction: Vertical/Horizontal, **Vertical Only**
 - RX Page Footer**
 - Off**
 - On
 - Continue Print. When Toner Is Nearly Out**
 - Off**
 - On
- Fax Settings**
 - ECM RX**
 - Off
 - On**
 - Incoming Ring**
 - Off
 - On**: Ring Times
 - 1 to **2** to 99 (times)
 - Remote RX**
 - Off
 - On**: Remote RX ID
 - 00 to **25** to 99
 - Auto RX Switch**
 - Off**
 - On: Incoming Ring Time
 - 1 to **15** to 99 (seconds)

Adjustment/Maintenance

- Special Processing**
 - Special Mode b**
 - Off, **Mode 1**, Mode 2, Mode 3, Mode 4
 - Special Mode c**
 - Off**, Mode 1, Mode 2, Mode 3
 - Special Mode d**
 - Off**, Mode 1, Mode 2
 - Special Mode h**
 - Off**, On
- Clean Fixing Unit**

System Management Settings

- System Manager Information Settings**
 - System Manager PIN**
 - Up to seven digits
 - System Manager Name**
 - Up to 32 characters
- Device Information Settings**
 - Device Name**
 - Up to 32 characters
 - Location**
 - Up to 32 characters
- Communication Management Settings**
 - Fax Settings**
 - TX Start Speed: **33600 bps**, 14400 bps, 9600 bps, 7200 bps, 4800 bps, 2400 bps
 - RX Start Speed: **33600 bps**, 14400 bps, 9600 bps, 7200 bps, 4800 bps, 2400 bps
 - Memory Lock Settings**
 - Off**
 - On
 - Memory Lock PIN
 - Report Print: Off, **On**
 - Memory Lock Time
 - Off**
 - On
 - Memory Lock Start Time
 - Memory Lock End Time
 - Select Country/Region**
 - United States (US)**, Canada (CA), Brazil (BR), Mexico (MX), Other
 - Restrict TX Function**
 - Address Book PIN**
 - Restrict New Destinations**
 - Off**, On
 - Allow Driver Faxing**
 - Off, **On**
 - Restrict Sending From History**
 - Off**, On
 - Fax No. Confirmation Re-Entry**
 - Off**, On
 - Restrict Sequential Broadcast**
 - Off**, Confirm Sequential Broadcast, Reject Sequential Broadcast
 - Display Job History**
 - Off, **On**
 - USB Device On/Off**
 - Off, **On**
 - Import/Export Address Book**
 - Update Firmware**
 - Initialize Address Book**
 - Initialize System Settings**
 - System Manager Information Settings**
 - Device Information Settings**
 - Communication Management Settings**
 - Restrict TX Function**
 - Display Job History**
 - USB Device On/Off**
 - Initialize All**

Timer Settings

- Time & Date Settings**
 - Date Display Type**
 - MM/DD/YYYY**
 - DD/MM YYYY
 - YYYY MM/DD
 - 12/24 Hour Clock**
 - 12 Hour (AM/PM)**, 24 Hour
 - Current Time Settings**
 - Daylight Savings**
 - Off**
 - On
 - Start (M/W/D), End (M/W/D)
 - Sleep Timer**
 - 3** to 240 (minutes)
 - Auto Reset Timer**
 - (0=Off, 1-9), 1 to **2** to 9 (minutes)

Initialize Menu

- Preferences**
- Timer Settings**
- Copy Settings**
- Fax TX Settings**
- Fax RX Settings**
- Special Processing**
- Initialize All**