
*** Network Configuration Page ***

1 Product Information

1- 1 Product Name G4070 series
1- 2 ROM Version 3.010
1- 3 Serial Number ABCD01234
1- 4 Default Password AaBbCcDd

2 Network Diagnostics

2- 1 Diagnostic Result There is a problem in the settings/environment.
2- 2 Result Codes C-0, C-7, C-9
2- 3 Result Code Details <http://canon.com/ijnwt>

3 Wireless LAN

Enable

3- 2 Infrastructure

Enable

3- 2- 1 Signal Strength 85[%]
3- 2- 2 Link Quality 90[%]
3- 2- 3 Frequency 5[GHz]

3- 2- 4 MAC Address AA:BB:CC:DD:EE:FF
3- 2- 5 Connection Active
3- 2- 6 SSID My Network
3- 2- 7 Channel 40
3- 2- 8 Encryption AES
3- 2- 9 WEP Key Length Inactive
3- 2-10 Authentication WPA2-PSK

3- 2-11 TCP/IPv4 Enable
3- 2-12 IP Address 192.168.0.105
3- 2-13 Subnet Mask 255.255.254.0
3- 2-14 Default Gateway 192.168.0.1

3- 2-15 TCP/IPv6 Enable

3- 2-16 Link Local Address aaaa::bbbb:cccc:dddd:eeee
3- 2-17 Link Local Prefix Length 64

3- 2-18 Stateless Address1
3- 2-19 Stateless Prefix Length1
3- 2-20 Stateless Address2
3- 2-21 Stateless Prefix Length2
3- 2-22 Stateless Address3
3- 2-23 Stateless Prefix Length3
3- 2-24 Stateless Address4
3- 2-25 Stateless Prefix Length4

3- 2-26 Default Gateway1
3- 2-27 Default Gateway2
3- 2-28 Default Gateway3
3- 2-29 Default Gateway4

3- 2-33 IPsec	Inactive
3- 2-34 Security Protocol	
3- 2-35 Wireless LAN DRX	Enable
3- 3 Wireless Direct	Disable
3- 3- 1 MAC Address	AA:BB:CC:DD:EE:FF
3- 3- 2 Connection	
3- 3- 3 SSID	
3- 3- 4 Password	
3- 3- 5 Channel	
3- 3- 6 Encryption	
3- 3- 7 Authentication	
3- 3- 8 TCP/IPv4	
3- 3- 9 IP Address	
3- 3-10 Subnet Mask	
3- 3-11 Default Gateway	
3- 3-12 TCP/IPv6	
3- 3-13 Link Local Address	
3- 3-14 Link Local Prefix Length	
3- 3-15 IPsec	
3- 3-16 Security Protocol	
3- 3-17 Wireless LAN DRX	
3- 3-18 Frequency	
5 Other Settings	
5- 1 Printer Name	000000000000
5- 2 Wireless Direct DevName	DIRECT-h695-G4070series
5- 4 WSD Printing	Enable
5- 5 WSD Timeout	15[min]
5- 6 LPD Printing	Enable
5- 7 RAW Printing	Enable
5- 9 Bonjour	Enable
5-10 Bonjour Service Name	Canon G4070 series
5-11 LLMNR	Enable
5-12 SNMP	Enable
5-13 PictBridge Commun.	Enable
5-14 DNS Server	Auto
5-15 Primary Server	1.2.3.4
5-16 Secondary Server	5.6.7.8
5-17 Proxy Server	Disable
5-18 Proxy Address	
5-19 Proxy Port	

5-20 Cert. Fingerprt(SHA-1)
5-21 Cert. Fingerprt(SHA-256)

00000000 00000000 00000000 00000000 00000000
00000000 00000000 00000000 00000000 00000000
00000000 00000000 00000000

7 Web Services

7- 1 Unsent Usage Logs
7- 2 Usage Log Last Sent
7- 3 Web Service Status
7- 4 Log Transmission Status

0
Registered
Active