

1 Product Information

1- 1 Product Name G5000 series
1- 2 ROM Version 1.000
1- 3 Serial Number ABCD12345

2 Network Diagnostics

2- 1 Diagnostic Result There is no problem.
2- 2 Result Codes c-0
2- 3 Result Code Details <http://canon.com/ijnwt>

3 Wireless LAN

Enable

3- 2 Infrastructure

Enable

3- 2- 1 Signal Strength 89 [%]
3- 2- 2 Link Quality 84 [%]
3- 2- 3 Frequency 2.4 [GHz]

3- 2- 4 MAC Address AA:AA:AA:AA:AA:AA
3- 2- 5 Connection Active
3- 2- 6 SSID My Network
3- 2- 7 Channel 3
3- 2- 8 Encryption AES
3- 2- 9 WEP Key Length Inactive
3- 2-10 Authentication WPA2-PSK

3- 2-11 TCP/IPv4 Enable
3- 2-12 IP Address 192.168.1.10
3- 2-13 Subnet Mask 255.255.255.0
3- 2-14 Default Gateway 192.168.1.1

3- 2-15 TCP/IPv6 Enable

3- 2-16 Link Local Address ffff::ffff:ffff:ffff:ffff
3- 2-17 Link Local Prefix Length 64

3- 2-18 Stateless Address1
3- 2-19 Stateless Prefix Length1
3- 2-20 Stateless Address2
3- 2-21 Stateless Prefix Length2
3- 2-22 Stateless Address3
3- 2-23 Stateless Prefix Length3
3- 2-24 Stateless Address4
3- 2-25 Stateless Prefix Length4

3- 2-26 Default Gateway1
3- 2-27 Default Gateway2
3- 2-28 Default Gateway3
3- 2-29 Default Gateway4

3- 2-33 IPsec Inactive

3- 2-34 Security Protocol

3- 3 Wireless Direct

Disable

3- 3- 1 MAC Address

AA:AA:AA:AA:AA:AA

3- 3- 2 Connection

3- 3- 3 SSID

3- 3- 4 Password

3- 3- 5 Channel

3- 3- 6 Encryption

3- 3- 7 Authentication

3- 3- 8 TCP/IPv4

3- 3- 9 IP Address

3- 3-10 Subnet Mask

3- 3-11 Default Gateway

3- 3-12 TCP/IPv6

3- 3-13 Link Local Address

3- 3-14 Link Local Prefix Length

3- 3-15 IPsec

3- 3-16 Security Protocol

4 Wired LAN

Disable

4- 1 MAC Address

AA:AA:AA:AA:AA:AA

4- 2 Connection

4- 3 TCP/IPv4

4- 4 IP Address

4- 5 Subnet Mask

4- 6 Default Gateway

4- 7 TCP/IPv6

4- 8 Link Local Address

4- 9 Link Local Prefix Length

4-10 Stateless Address1

4-11 Stateless Prefix Length1

4-12 Stateless Address2

4-13 Stateless Prefix Length2

4-14 Stateless Address3

4-15 Stateless Prefix Length3

4-16 Stateless Address4

4-17 Stateless Prefix Length4

4-18 Default Gateway1

4-19 Default Gateway2

4-20 Default Gateway3

4-21 Default Gateway4

4-25 IPsec

4-26 Security Protocol

4-27 Wired LAN DRX

5 Other Settings

5- 1 Printer Name	AAAAAA000000
5- 2 Wireless Direct DevName	DIRECT-xxF1-G5000series
5- 4 WSD Printing	Enable
5- 5 WSD Timeout	15[min]
5- 6 LPD Printing	Enable
5- 7 RAW Printing	Enable
5- 9 Bonjour	Enable
5-10 Bonjour Service Name	Canon G5000 series
5-11 LLMNR	Enable
5-12 SNMP	Enable
5-13 PictBridge Commun.	Enable
5-14 DNS Server	Auto
5-15 Primary Server	
5-16 Secondary Server	
5-17 Proxy Server	Disable
5-18 Proxy Address	
5-19 Proxy Port	
5-20 Cert. Fingerprt (SHA-1)	12345678 12345678 12345678 12345678 12345678
5-21 Cert. Fingerprt (SHA-256)	12345678 12345678 12345678 12345678 12345678 12345678 12345678 12345678