

1 Product Information

1- 1 Product Name G6000 series  
1- 2 ROM Version 1.000  
1- 3 Serial Number ABCD12345

2 Network Diagnostics

2- 1 Diagnostic Result There is no problem.  
2- 2 Result Codes c-0  
2- 3 Result Code Details <http://canon.com/ijnwt>

3 Wireless LAN

Enable

3- 2 Infrastructure

Enable

3- 2- 1 Signal Strength 100[%]  
3- 2- 2 Link Quality 100[%]  
3- 2- 3 Frequency 2.4 [GHz]

3- 2- 4 MAC Address AA:AA:AA:AA:AA:AA  
3- 2- 5 Connection Active  
3- 2- 6 SSID My Network  
3- 2- 7 Channel 1  
3- 2- 8 Encryption AES  
3- 2- 9 WEP Key Length Inactive  
3- 2-10 Authentication WPA2-PSK

3- 2-11 TCP/IPv4 Enable  
3- 2-12 IP Address 192.168.1.200  
3- 2-13 Subnet Mask 255.255.255.0  
3- 2-14 Default Gateway 192.168.1.1

3- 2-15 TCP/IPv6 Enable

3- 2-16 Link Local Address ffff::ffff:ffff:ffff:ffff  
3- 2-17 Link Local Prefix Length 64

3- 2-18 Stateless Address1  
3- 2-19 Stateless Prefix Length1  
3- 2-20 Stateless Address2  
3- 2-21 Stateless Prefix Length2  
3- 2-22 Stateless Address3  
3- 2-23 Stateless Prefix Length3  
3- 2-24 Stateless Address4  
3- 2-25 Stateless Prefix Length4

3- 2-26 Default Gateway1  
3- 2-27 Default Gateway2  
3- 2-28 Default Gateway3  
3- 2-29 Default Gateway4

3- 2-33 IPsec Inactive

3- 2-34 Security Protocol

- 3- 3 Wireless Direct Disable
- 3- 3- 1 MAC Address AA:AA:AA:AA:AA:AA
- 3- 3- 2 Connection
- 3- 3- 3 SSID
- 3- 3- 4 Password
- 3- 3- 5 Channel
- 3- 3- 6 Encryption
- 3- 3- 7 Authentication
  
- 3- 3- 8 TCP/IPv4
- 3- 3- 9 IP Address
- 3- 3-10 Subnet Mask
- 3- 3-11 Default Gateway
  
- 3- 3-12 TCP/IPv6
  
- 3- 3-13 Link Local Address
- 3- 3-14 Link Local Prefix Length
  
- 3- 3-15 IPsec
- 3- 3-16 Security Protocol

4 Wired LAN

- 4- 1 MAC Address Disable
- 4- 2 Connection AA:AA:AA:AA:AA:AA
- 4- 3 TCP/IPv4
- 4- 4 IP Address
- 4- 5 Subnet Mask
- 4- 6 Default Gateway
  
- 4- 7 TCP/IPv6
  
- 4- 8 Link Local Address
- 4- 9 Link Local Prefix Length
  
- 4-10 Stateless Address1
- 4-11 Stateless Prefix Length1
- 4-12 Stateless Address2
- 4-13 Stateless Prefix Length2
- 4-14 Stateless Address3
- 4-15 Stateless Prefix Length3
- 4-16 Stateless Address4
- 4-17 Stateless Prefix Length4
  
- 4-18 Default Gateway1
- 4-19 Default Gateway2
- 4-20 Default Gateway3
- 4-21 Default Gateway4
  
- 4-25 IPsec
- 4-26 Security Protocol
  
- 4-27 Wired LAN DRX

## 5 Other Settings

|                               |  |
|-------------------------------|--|
| 5- 1 Printer Name             | AAAAAA000000   |
| 5- 2 Wireless Direct DevName  | DIRECT-AAAA-G6000series  |
| 5- 4 WSD Printing             | Enable   |
| 5- 5 WSD Timeout              | 15[min]  |
| 5- 6 LPD Printing             | Enable   |
| 5- 7 RAW Printing             | Enable   |
| 5- 9 Bonjour                  | Enable   |
| 5-10 Bonjour Service Name     | Canon G6000 series   |
| 5-11 LLMNR                    | Enable   |
| 5-12 SNMP                     | Enable   |
| 5-13 PictBridge Commun.       | Enable   |
| 5-14 DNS Server               | Auto   |
| 5-15 Primary Server           | 192.168.1.1  |
| 5-16 Secondary Server         |  |
| 5-17 Proxy Server             | Disable  |
| 5-18 Proxy Address            |  |
| 5-19 Proxy Port               |  |
| 5-20 Cert. Fingerprt(SHA-1)   | 12345678 12345678 12345678 12345678 12345678                               |
| 5-21 Cert. Fingerprt(SHA-256) | 12345678 12345678 12345678 12345678 12345678<br>12345678 12345678 12345678 |