

Menu Route Map

Direct Connection

Network Settings

- Select Wired/Wireless LAN
 - Wired LAN, Wireless LAN
- Wireless LAN Settings
 - SSID Settings
 - Select Access Point
 - Enter Manually
 - Security Settings
 - None
 - WEP (802.11 Authentication)
 - Open System, Shared key
 - WPA/WPA2-PSK (WPA/WPA2 Encryption)
 - Auto, AES-CCMP
 - WPS Push Button Mode
 - WPS PIN Code Mode
 - Power Save Mode
 - Off, On
 - Wireless LAN Information
 - MAC Address
 - Wireless LAN Status
 - Latest Error Information
 - Channel
 - SSID Settings
 - Security Settings
 - Power Save Mode

Direct Connection Settings

- Use Direct Connection
 - Off, On
 - Direct Connection Only
 - Wireless LAN/Direct Conn. (Auto Switch)
- Time Until Direct Connection Termination
 - 0=Off, 1 to 10 to 60 (min.)
- Access Point Mode Settings
 - Use Custom SSID
 - Off, On
 - Use Custom Network Key
 - Off, On

TCP/IP Settings

IPv4 Settings

- IP Address Settings
 - Auto Acquire
 - Select Protocol
 - Off, DHCP, BOOTP, RARP
 - Auto IP
 - Off, On
 - Manually Acquire
 - IP Address: 0.0.0.0
 - Subnet Mask: 0.0.0.0
 - Gateway Address: 0.0.0.0
 - Check Settings
 - Auto Acquire
 - IP Address
 - Subnet Mask
 - Gateway Address
- PING Command
- DNS Settings
 - DNS Server Settings
 - Primary DNS Server: 0.0.0.0
 - Secondary DNS Server: 0.0.0.0
 - DNS Host Name/Domain Name Settings
 - Host Name
 - Domain Name
 - DNS Dynamic Update Settings
 - Off, On (DNS Dyn. Updt. Intrvl.)
 - 0 to 24 to 48 (hr.)
- mDNS Settings
 - Off, On (mDNS Name)
- DHCP Option Settings
 - Acquire Host Name
 - Off, On
 - DNS Dynamic Update
 - Off, On

IPv6 Settings

- Use IPv6
 - Off, On, Check Settings
 - Link-Local Address
 - Prefix Length
- Stateless Address Settings
 - Off, On, Check Settings
 - Stateless Address
 - Prefix Length
- Use DHCPv6
 - Off, On, Check Settings
 - Stateful Address
 - Prefix Length
- DNS Settings
 - DNS Host Name/Domain Name Settings (Use IPv4 Host/Domain)
 - Off, On
 - Host Name
 - Domain Name
 - DNS Dynamic Update Settings
 - Off, On
 - Register Manual Address
 - Off, On
 - Register Stateful Address
 - Off, On
 - Register Stateless Address
 - Off, On
 - DNS Dynamic Update Interval
 - 0 to 24 to 48 (hr.)
- mDNS Settings
 - Off, On (Use IPv4 Name for mDNS)
 - Off (mDNS Name), On

LPD Print Settings

- Off, On

RAW Print Settings

- Off, On

WSD Settings

- WSD Print Settings
 - Use WSD Print
 - Off, On
 - Use WSD Browsing
 - Off, On
- WSD Scan Settings
 - Use WSD Scan
 - Off, On
 - Use Computer Scan
 - Off, On
 - Use Multicast Discovery
 - Off, On

Use HTTP

- Off, On

Port Number Settings

- LPD
 - 1 to 515 to 65535
- RAW
 - 1 to 9100 to 65535
- WSD Multicast Discovery
 - 1 to 3702 to 65535
- HTTP
 - 1 to 80 to 65535
- SNMP
 - 1 to 161 to 65535

MTU Size

- 1300, 1400, 1500

SNMP Settings

- SNMPv1 Settings
 - Off, On
 - Community Name 1 Settings
 - Off, On
 - Community Name
 - MIB Access Permission
 - Community Name 2 Settings
 - Off, On
 - Community Name
 - MIB Access Permission
 - Dedicated Community Settings
 - Off, On
- SNMPv3 Settings
 - Off, On
- Acquire Printer Mngt. Info. from Host
 - Off, On

Dedicated Port Settings

- Off, On

Waiting Time for Connection at Startup

- 0 to 300 (sec.)

Ethernet Driver Settings

- Auto Detect
 - Off, On
 - Communication Mode
 - Half Duplex, Full Duplex
 - Ethernet Type
 - 10BASE-T, 100BASE-TX
- Mac Address

IEEE 802.1X Settings

- Off, On

Initialize Network Settings

Output Reports

- Consumables Status Report
- Eco Report
- User Data List
- PCL Font List*

Settings marked with an asterisk (*) are only available for MF244dw.

Preferences

Display Settings

- Contrast
 - 5 Levels
- Invert Screen Colors
 - Off, On
- Millimeter/Inch Entry Switch
 - Millimeter, Inch
- Notify to Check Paper Settings
 - Off, On
- Gram/Pound Switch
 - Gram, Pound
- Notify to Clean Original Scanning Area*
 - Off, On
- Message Display Time
 - 1 to 2 to 5 (sec.)
- Scrolling Speed
 - Slow, Standard, Fast
- Cursor Movement Type
 - Auto, Manual
- Language
 - Chinese (Simplified), Chinese (Traditional), English, French, German, Italian, Japanese, Korean, Portuguese, Spanish
- Remote UI Language
 - Chinese (Simplified), Chinese (Traditional), English, French, German, Italian, Japanese, Korean, Portuguese, Spanish

Settings marked with an asterisk (*) are only available for MF244dw.

Timer Settings

Quiet Mode Time

- Start Time
 - Off, On
 - Start time setting to enter quiet mode
- End Time
 - Off, On
 - Stop time setting to exit quiet mode

Date/Time Settings

- Date Format
 - YYYY MM/DD, MM/DD/YYYY, DD/MM/YYYY
- Time Format
 - 12 Hour (AM/PM), 24 Hour
- Current Date/Time Settings
- Time Zone
 - (UTC-12:00) International Date Line West to (UTC-05:00) Eastern Time (US & Canada) to (UTC+14:00) Kiritimati Island
- Daylight Saving Time Settings
 - Off, On
 - Start: Month, Day
 - End: Month, Day

Auto Sleep Time

- 1 to 30 (min.)

Auto Reset Time

- 0=Off (Auto Reset is disabled.), 1 to 2 to 9 (min.)

Function After Auto Reset

- Default Function, Selected Function

Auto Offline Time

- 0=Off (The machine remains online.), 1 to 5 to 60 (min.)

Common Settings*

Switch Paper Feed Method

- Multi-Purpose Tray
 - Speed Priority, Print Side Priority
- Drawer 1
 - Speed Priority, Print Side Priority

Settings marked with an asterisk (*) are only available for MF244dw / MF242dw.

Copy Settings

Change Default Settings

- Number of Copies
 - 1 to 999
- Density
 - 4 to 0 to +4, Auto Density
- Original Type
 - Text, Text/Photo (High Speed), Text/Photo, Photo
- 2-Sided*
 - Off, 1->2-Sided, Original/Finishing Type
- Copy Ratio
 - Custom Ratio, 100% (Direct), 400% (Max), 200%, 129% STMT-LTR, 78% LGL-LTR, 64% LTR-STMT, 50%, 25%(Min)
- N on 1
 - Off, 2 on 1, 4 on 1, ID Card Copy, Select Layout
- Collate
 - Off, On
- Sharpness
 - 7 Levels

Correct Density

- 4 to 0 to +4

Initialize Default Settings

Settings marked with an asterisk (*) are only available for MF244dw / MF242dw.

Scan Settings

Shortcut Key Settings (MF244dw / MF242dw)

- Register
 - Scan -> PC
 - Off
 - USB Connection
 - Color Scan, B&W Scan, Custom 1, Custom 2
 - Network Connection
 - Color Scan, B&W Scan, Custom 1, Custom 2
 - Confirm Destination
 - Scan -> PC

Shortcut Key Settings (MF232w)

- Register
 - Scan -> PC1
 - Off
 - USB Connection
 - Color Scan, B&W Scan, Custom 1, Custom 2
 - Network Connection
 - Color Scan, B&W Scan, Custom 1, Custom 2
 - Scan -> PC2
 - Off
 - USB Connection
 - Color Scan, B&W Scan, Custom 1, Custom 2
 - Network Connection
 - Color Scan, B&W Scan, Custom 1, Custom 2
 - Confirm Destination
 - Scan -> PC1
 - Scan -> PC2

Printer Settings

Action When Paper Size Mismatch

- Force Output, Display Error

Mobile Print Halftones

- Gradation, Error Diffusion

Copies*

- 1 to 999

2-Sided Printing*

- Off, On

Default Paper*

- Print Quality
 - Density*
 - 17 Levels
 - Fine Adjust
 - High: 17 Levels
 - Medium: 17 Levels
 - Low: 17 Levels

- Toner Save
- Off, On
- Special Print Mode*
- Off, Special Settings 1, Special Settings 2
- Resolution*
- 1200 dpi, 600 dpi
- Density Fine Adjustment*
- 1 to 0 to 1

Layout*

- Binding Location
 - Long Edge, Short Edge

Timeout*

- 5 to 15 to 300 (sec.)

PCL*

- Paper Save
 - Off, On
- Orientation
 - Portrait, Landscape
- Font Number
 - 0 to 54
- Point Size
 - 4.00 to 12.00 to 999.75 (point)
- Pitch
 - 0.44 to 10.00 to 99.99 (cpi)
- Form Lines
 - 5 to 60 to 128 (lines)
- Character Code
 - DESKTOP, ISO4, ISO6, ISO11, ISO15, ISO17, ISO21, ISO60, ISO69, ISOL1, ISOL2, ISOL5, ISOL6, LEGAL, MATHS, MCTEXT, MSPUBL, PC775, PC8, PC850, PC852, PC8BDN, PC8TK, PC1004, PIFONT, PSMATH, PSTEXT, ROMANS, VNINTL, VNMMATH, VNUS, WIN30, WINBALT, WINL1, WINL2, WINL5
- Custom Paper
 - Off, On
- Unit of Measure
 - Millimeters, Inches
- X dimension
 - 3 to 8 1/2 (inches) or 77 to 216 (mm)
- Y dimension
 - 5 to 14 (inches) or 127 to 356 (mm)
- Append CR to LF
 - Yes, No
- Enlarge A4 Print Width
 - Off, On
- Halftones
 - Text
 - Color Tone, Gradation, Resolution
 - Graphics
 - Color Tone, Gradation, Resolution
 - Images
 - Color Tone, Gradation, Resolution

Settings marked with an asterisk (*) are only available for the MF244dw.

Adjustment/Maintenance

Displ. Timing for Cartridge Prep. Notif.

- 1 to 10 to 99 (%)

Toner Save

- Copy
 - Off, On

Special Processing

- Special Printing Mode U
 - Off, On
- Special Printing Mode V
 - Off, Mode 1, Mode 2, Mode 3
- Special Printing Mode X
 - Off, Mode 1, Mode 2, Mode 3, Mode 4
- Special Printing Mode Z
 - Off, Mode 1, Mode 2, Mode 3, Mode 4
- Special Printing Mode B
 - Off, Mode 1, Mode 2, Mode 3
- Special Printing Mode C
 - Off, On
- Special Printing Mode D
 - Copy
 - Off, On
 - Print
 - Off, On
- Special Printing Mode I
 - Off, On
- Special Printing Mode J
 - Off, On
- Special Printing Mode K
 - Off, On

Clean Fixing Assembly

System Management Settings

Network Settings

- Network Settings

System Manager Information Settings

- System Manager PIN
- System Manager Name

Device Information Settings

- Device Name
- Location

Security Settings

- Use TLS
 - Off, On
- IPv4 Address Filter
 - Off, On
- IPv6 Address Filter
 - Off, On
- MAC Address Filter
 - Off, On

Select Country/Region

- United States (US), Canada (CA), Brazil (BR), Mexico (MX), Other

Remote UI Settings

- Use Remote UI
 - Off, On
- Remote UI Access Security Settings
 - Off, On

Auto Online for Remote Scan

- Off, On

Use as USB Device

- Off, On

Enable Product Extended Survey Program

- Off, On

Displ. Consumb. Info (RUI/Toner Status)

- Displ. Consumables Purchase Button (RUI)
 - Off, On
- Toner Status Settings
 - Off, On (Displ. Purchase Button)
 - Off, On

Google Cloud Print Settings

- Enable Google Cloud Print
 - Off, On
- Google Cloud Print Registration Status

PDL Selection (Plug and Play)

- Network
 - UFRIII LT, UFRIII LT (V4), PCL6*1
- USB
 - UFRIII LT, UFRIII LT (V4), PCL6*1

Update Firmware

- Via PC, Via Internet, Version Information

Initialize Eco Report Counter

Initialize Menu

- Preferences
- Timer Settings
- Common Settings*2
- Copy Settings
- Scan Settings
- Printer Settings
- Adjustment/Maintenance
- System Management Settings
 - Network Settings
 - System Manager Information Settings
 - Device Information Settings
 - Security/Remote UI Settings
 - Auto Online for Remote Scan
 - Use as USB Device
 - Enable Product Extended Survey Program
 - Displ. Consumb. Info (RUI/Toner Status)
 - Google Cloud Print Settings
 - PDL Selection (Plug and Play)
 - Initialize All
- Initialize All

Initialize All Data/Settings

Settings marked with "*"1 are only available for the MF244dw.
Settings marked with "*"2 are only available for the MF244dw / MF242dw.