
*** Network Configuration Page ***

Wireless LAN Enable
Connection Inactive
MAC Address AA:BB:CC:DD:EE:FF
SSID BJNPSETUP
Password
Communication Mode Infrastructure
Channel
Encryption none
WEP Key Length Inactive
Authentication open
Signal Strength 0[%]
TCP/IP Version IPv4 & IPv6
IPv4 IP Address
IPv4 Default Gateway
Subnet Mask
IPv6 IP Address
IPv6 Default Gateway
Subnet Prefix Length
IPsec
Security Protocol
Wireless LAN DRX Enable

Wired LAN Disable
Connection Inactive
MAC Address FF:EE:DD:CC:BB:AA
TCP/IP Version IPv4 & IPv6
IPv4 IP Address
IPv4 Default Gateway
Subnet Mask
IPv6 IP Address
IPv6 Default Gateway
Subnet Prefix Length
IPsec
Security Protocol
Wired LAN DRX

Other Settings
Printer Name 000000000000
Shared Memory Card Enable
WSD Enable
WSD Timeout 1[min]
LPR Protocol Enable
Bonjour Enable
Bonjour Service Name Canon MG7500 series
PictBridge Commun. Enable
DNS Server Auto
Primary Server
Secondary Server
Proxy Server Disable
Proxy Port
Proxy Address