

Wireless LAN                    Enable  
  Connection                    Active  
  MAC Address                    11:22:33:44:55:66  
  
  SSID                            141610-MG2900series  
  Password                        ABCD01234  
  Communication Mode            Access Point Mode  
  Channel                         3  
  Encryption                     AES  
  WEP Key Length                 WPA2-PSK  
  Authentication  
  Signal Strength  
  
  TCP/IP Version                 IPv4 & IPv6  
  IPv4 IP Address                 192.168.114.1  
  IPv4 Default Gateway           192.168.114.1  
  Subnet Mask                    255.255.255.0  
  IPv6 IP Address                 FE80:0000:0000:0000:0000:0000:0000:0000  
  IPv6 Default Gateway  
  Subnet Prefix Length            64  
  
  IPsec  
  Security Protocol  
  WPS PIN CODE                    00000000  
  Wireless LAN DRX

Other Settings  
  Printer Name                    000000000000  
  WSD                             Enable  
  WSD Timeout                    1[min]  
  LPR Protocol                    Enable  
  
  Bonjour  
  Bonjour Service Name            Canon MG2900 series  
  PictBridge Commun.             Enable  
  DNS Server  
  Primary Server  
  Secondary Server  
  Proxy Server  
  Proxy Port  
  Proxy Address