
*** Network Configuration Page ***

Wireless LAN Disable
 Connection Inactive
 MAC Address AA:BB:CC:DD:EE:FF

 SSID
 Communication Mode
 Channel
 Encryption
 WEP Key Length
 Authentication
 Signal Strength

 TCP/IP Version IPv4 & IPv6
 IPv4 IP Address
 IPv4 Default Gateway
 Subnet Mask
 IPv6 IP Address
 IPv6 Default Gateway
 Subnet Prefix Length

 IPsec
 Security Protocol
 WPS PIN CODE 12345678
 Wireless LAN DRX

Wired LAN Enable
 Connection Inactive
 MAC Address AA:BB:CC:DD:EE:FF

 TCP/IP Version IPv4 & IPv6
 IPv4 IP Address
 IPv4 Default Gateway
 Subnet Mask
 IPv6 IP Address
 IPv6 Default Gateway
 Subnet Prefix Length

 IPsec
 Security Protocol
 Wired LAN DRX Enable

Other Settings
 Printer Name 000000000000
 WSD Enable
 WSD Timeout 1 [min]
 LPR Protocol Enable

 Bonjour
 Bonjour Service Name Enable
 Canon iX6800 series
 DNS Server Manual
 Primary Server
 Secondary Server
 Proxy Server Disable
 Proxy Port
 Proxy Address

 IP Address Filtering Disable