
*** Network Configuration Page ***

Wireless LAN Enable
 Connection Active
 MAC Address AA:BB:CC:DD:EE:FF

 SSID Home
 Communication Mode Infrastructure
 Channel 9
 Encryption AES
 WEP Key Length Inactive
 Authentication WPA2-PSK
 Signal Strength 100[%]

 TCP/IP Version IPv4
 IPv4 IP Address 192.168.0.103
 IPv4 Default Gateway 192.168.0.1
 Subnet Mask 255.255.255.0
 IPv6 IP Address
 IPv6 Default Gateway
 Subnet Prefix Length

 IPsec
 Security Protocol
 WPS PIN CODE 12345678
 Wireless LAN DRX Enable

Wired LAN Disable
 Connection Inactive
 MAC Address AA:BB:CC:DD:EE:FF

 TCP/IP Version IPv4
 IPv4 IP Address
 IPv4 Default Gateway
 Subnet Mask
 IPv6 IP Address
 IPv6 Default Gateway
 Subnet Prefix Length

 IPsec
 Security Protocol
 Wired LAN DRX

Other Settings
 Printer Name 000000000000
 WSD Enable
 WSD Timeout 1 [min]
 LPR Protocol Enable

 Bonjour Enable
 Bonjour Service Name Canon iX6800 series

 DNS Server Auto
 Primary Server 192.168.0.1
 Secondary Server
 Proxy Server Disable
 Proxy Port
 Proxy Address

 IP Address Filtering Disable

Default Password