

Wireless LAN Enable
 Connection Inactive
 MAC Address AA:BB:CC:DD:EE:FF
 SSID BJNPSETUP
 Communication Mode Infrastructure
 Channel
 Encryption none
 WEP Key Length Inactive
 Authentication open
 Signal Strength 0[%]
 TCP/IP Version IPv4 & IPv6
 IPv4 IP Address
 IPv4 Default Gateway
 Subnet Mask
 IPv6 IP Address
 IPv6 Default Gateway
 Subnet Prefix Length
 IPsec
 Security Protocol
 Wireless LAN DRX Enable

Wired LAN Disable
 Connection Inactive
 MAC Address FF:EE:DD:CC:BB:AA
 TCP/IP Version IPv4 & IPv6
 IPv4 IP Address
 IPv4 Default Gateway
 Subnet Mask
 IPv6 IP Address
 IPv6 Default Gateway
 Subnet Prefix Length
 IPsec
 Security Protocol
 Wired LAN DRX

Other Settings
 Printer Name 000000000000
 Shared Memory Card Enable
 WSD Enable
 WSD Timeout 1[min]
 LPR Protocol Enable
 Bonjour Enable
 Bonjour Service Name Canon MG7100 series
 PictBridge Commun. Enable
 DNS Server Auto
 Primary Server
 Secondary Server
 Proxy Server Disable
 Proxy Port
 Proxy Address
 IP Address Filtering Disable