
*** Network Configuration Page ***

Product Information

Product Name MG3600 series
ROM Version 3.000
Serial Number ABCD01234
Default Password AbCd1234

Wireless LAN

Enable
MAC Address 00:11:22:33:44:55
WPS PIN CODE 01234567

Infrastructure

Enable
Connection Inactive
SSID BJNPSETUP
Channel
Encryption none
WEP Key Length Inactive
Authentication open

Signal Strength 0[%]

TCP/IPv4 Enable

IP Address
Subnet Mask
Default Gateway

TCP/IPv6 Enable

IP Address
Subnet Prefix Length
Default Gateway

IPsec Inactive
Security Protocol

Access Point Mode

Disable

Connection
SSID
Password
Channel
Encryption
Authentication

TCP/IPv4
IP Address
Subnet Mask
Default Gateway

TCP/IPv6
IP Address
Subnet Prefix Length
Default Gateway

IPsec
Security Protocol

Other Settings

Printer Name	000000000000
WSD Printing	Enable
WSD Timeout	5 [min]
LPD Printing	Enable
Bonjour	Enable
Bonjour Service Name	Canon MG3600 series
PictBridge Commun.	Enable
DNS Server	Auto
Primary Server	
Secondary Server	
Proxy Server	Disable
Proxy Address	
Proxy Port	