
*** Network Configuration Page ***

Product Information

Product Name	MG7700 series
ROM Version	2.000
Serial Number	ABCD12345

Wireless LAN

Enable	Enable
MAC Address	AA:BB:CC:DD:EE:FF

Infrastructure

Enable	Enable
Connection	Active
SSID	My_Network
Channel	1
Encryption	AES
WEP Key Length	Inactive
Authentication	WPA2-PSK

Signal Strength	72[%]
-----------------	-------

TCP/IPv4	Enable
IP Address	192.168.1.15
Subnet Mask	255.255.255.0
Default Gateway	192.168.1.1

TCP/IPv6	Enable
IP Address	1234::1234:1234:1234:1234
Subnet Prefix Length	64
Default Gateway	

IPsec	Inactive
Security Protocol	

Direct Connection

Disable

Connection	
SSID	
Password	
Channel	
Encryption	
Authentication	

TCP/IPv4	
IP Address	
Subnet Mask	
Default Gateway	

TCP/IPv6	
IP Address	
Subnet Prefix Length	
Default Gateway	

IPsec

Security Protocol

Wired LAN	Disable
MAC Address	AA:BB:CC:DD:EE:FF
Connection	
TCP/IPv4	
IP Address	
Subnet Mask	
Default Gateway	
TCP/IPv6	
IP Address	
Subnet Prefix Length	
Default Gateway	
IPsec	
Security Protocol	
Wired LAN DRX	
Other Settings	
Printer Name	000000000000
Direct Conn. DevName	AAAAAA-MG7700series
WSD Printing	Enable
WSD Timeout	1 [min]
LPD Printing	Enable
Bonjour	Enable
Bonjour Service Name	Canon MG7700 ABC
PictBridge Commun.	Enable
DNS Server	Auto
Primary Server	0.0.0.0
Secondary Server	0.0.0.0
Proxy Server	Disable
Proxy Address	
Proxy Port	