
*** Network Configuration Page ***

Product Information

Product Name MG3000 series
ROM Version 1.000
Serial Number ABCD01234

Wireless LAN Enable
WPS PIN CODE 00000000

Infrastructure Enable
MAC Address 00:00:00:00:00:00
Connection Inactive
SSID BJNPSETUP
Channel
Encryption none
WEP Key Length Inactive
Authentication none

Signal Strength 0[%]

TCP/IPv4 Enable
IP Address
Subnet Mask
Default Gateway

TCP/IPv6 Enable

Link Local Address
Link Local Prefix Length

Stateless Address1
Stateless Prefix Length1
Stateless Address2
Stateless Prefix Length2
Stateless Address3
Stateless Prefix Length3
Stateless Address4
Stateless Prefix Length4

Default Gateway1
Default Gateway2
Default Gateway3
Default Gateway4

IPsec Inactive
Security Protocol

Access Point Mode Disable
MAC Address 00:00:00:00:00:00

Connection
SSID
Password
Channel
Encryption
Authentication

TCP/IPv4
IP Address
Subnet Mask
Default Gateway

TCP/IPv6

Link Local Address
Link Local Prefix Length

IPsec
Security Protocol

Other Settings

Printer Name	000000000000
WSD Printing	Enable
WSD Timeout	15[min]
LPD Printing	Enable
RAW Printing	Enable
Bonjour	Enable
Bonjour Service Name	Canon MG3000 series
LLMNR	Enable
SNMP	Enable
PictBridge Commun.	Enable
DNS Server	Auto
Primary Server	
Secondary Server	
Proxy Server	Disable
Proxy Address	
Proxy Port	
Cert. Fingerprt (SHA-1)	
Cert. Fingerprt (SHA-256)	