

\*\*\*\*\*  
\*\*\* Network Configuration Page \*\*\*  
\*\*\*\*\*

Product Information

Product Name TS6000 series  
ROM Version 1.090  
Serial Number ABCD12345

Wireless LAN Disable

Infrastructure Disable  
MAC Address 00:00:00:00:00:00  
Connection  
SSID  
Channel  
Encryption  
WEP Key Length  
Authentication

Signal Strength

TCP/IPv4  
IP Address  
Subnet Mask  
Default Gateway

TCP/IPv6

Link Local Address  
Link Local Prefix Length

Stateless Address1  
Stateless Prefix Length1  
Stateless Address2  
Stateless Prefix Length2  
Stateless Address3  
Stateless Prefix Length3  
Stateless Address4  
Stateless Prefix Length4

Default Gateway1  
Default Gateway2  
Default Gateway3  
Default Gateway4

IPsec  
Security Protocol

Wireless Direct Disable  
MAC Address 00:00:00:00:00:00  
Connection  
SSID  
Password

Channel  
Encryption  
Authentication

TCP/IPv4  
IP Address  
Subnet Mask  
Default Gateway

TCP/IPv6

Link Local Address  
Link Local Prefix Length

IPsec  
Security Protocol

Other Settings

Printer Name 000000000000  
Wireless Direct DevName ABCDEF-TS6000series

WSD Printing Enable  
WSD Timeout 15[min]

LPD Printing Enable  
RAW Printing Enable

Bonjour Enable  
Bonjour Service Name Canon TS6000 series

LLMNR Enable  
SNMP Enable

PictBridge Commun. Enable

DNS Server  
Primary Server  
Secondary Server  
Proxy Server  
Proxy Address  
Proxy Port

Cert. Fingerprt(SHA-1)  
Cert. Fingerprt(SHA-256)