
*** Network Configuration Page ***

Product Information

Product Name TS5000 series
ROM Version 1.090
Serial Number ABCD01234

Wireless LAN Disable

Infrastructure Disable
MAC Address 00:00:00:00:00:00
Connection
SSID
Channel
Encryption
WEP Key Length
Authentication

Signal Strength

TCP/IPv4
IP Address
Subnet Mask
Default Gateway

TCP/IPv6

Link Local Address
Link Local Prefix Length

Stateless Address1
Stateless Prefix Length1
Stateless Address2
Stateless Prefix Length2
Stateless Address3
Stateless Prefix Length3
Stateless Address4
Stateless Prefix Length4

Default Gateway1
Default Gateway2
Default Gateway3
Default Gateway4

IPsec
Security Protocol

Wireless Direct Disable
MAC Address 00:00:00:00:00:00
Connection
SSID
Password

Channel
Encryption
Authentication

TCP/IPv4
IP Address
Subnet Mask
Default Gateway

TCP/IPv6

Link Local Address
Link Local Prefix Length

IPsec
Security Protocol

Other Settings

Printer Name 000000000000
Wireless Direct DevName ABCDEF-TS5000series

WSD Printing Enable
WSD Timeout 15[min]

LPD Printing Enable
RAW Printing Enable

Bonjour Enable
Bonjour Service Name Canon TS5000 series

LLMNR Enable
SNMP Enable

PictBridge Commun. Enable

DNS Server
Primary Server
Secondary Server
Proxy Server
Proxy Address
Proxy Port

Cert. Fingerprt(SHA-1)
Cert. Fingerprt(SHA-256)