
*** Network Configuration Page ***

Product Information

Product Name G4000 series
ROM Version 1.010
Serial Number ABCD12345

Wireless LAN Enable

Infrastructure Enable
MAC Address 00:00:00:00:00:00
Connection Inactive
SSID BJNPSETUP
Channel
Encryption none
WEP Key Length Inactive
Authentication none

Signal Strength 0[%]

TCP/IPv4 Enable
IP Address
Subnet Mask
Default Gateway

TCP/IPv6 Enable

Link Local Address
Link Local Prefix Length

Stateless Address1
Stateless Prefix Length1
Stateless Address2
Stateless Prefix Length2
Stateless Address3
Stateless Prefix Length3
Stateless Address4
Stateless Prefix Length4

Default Gateway1
Default Gateway2
Default Gateway3
Default Gateway4

IPsec Inactive
Security Protocol

Wireless Direct Disable
MAC Address 00:00:00:00:00:00
Connection
SSID
Password

Channel
Encryption
Authentication

TCP/IPv4
IP Address
Subnet Mask
Default Gateway

TCP/IPv6

Link Local Address
Link Local Prefix Length

IPsec
Security Protocol

Other Settings

Printer Name 754B31000000
Wireless Direct DevName 754B31-G4000series

WSD Printing Enable
WSD Timeout 15[min]

LPD Printing Enable
RAW Printing Enable

Bonjour Enable
Bonjour Service Name Canon G4000 series

LLMNR Enable
SNMP Enable

DNS Server Auto
Primary Server
Secondary Server
Proxy Server Disable
Proxy Address
Proxy Port

Cert. Fingerprt (SHA-1)
Cert. Fingerprt (SHA-256)