
*** Network Configuration Page ***

Product Information

Product Name MB5100 series
ROM Version 1.050
Serial Number ABCD12345

Wireless LAN

Enable
MAC Address 00:00:0:0:00:00

Infrastructure

Enable
Connection Inactive
SSID BJNPSETUP
Channel
Encryption none
WEP Key Length Inactive
Authentication none

Signal Strength 0[%]

TCP/IPv4 Enable
IP Address
Subnet Mask
Default Gateway

TCP/IPv6 Enable

Link Local Address
Link Local Prefix Length

Stateless Address1
Stateless Prefix Length1
Stateless Address2
Stateless Prefix Length2
Stateless Address3
Stateless Prefix Length3
Stateless Address4
Stateless Prefix Length4

Default Gateway1
Default Gateway2
Default Gateway3
Default Gateway4

IPsec Inactive
Security Protocol

Direct Connection

Disable
Connection
SSID
Password
Channel

WSD Timeout	1 [min]
LPD Printing	Enable
RAW Printing	Enable
Bonjour	Enable
Bonjour Service Name	Canon MB5100 series
LLMNR	Enable
SNMP	Enable
DNS Server	Auto
Primary Server	
Secondary Server	
Proxy Server	Disable
Proxy Address	
Proxy Port	
Cert. Fingerprt (SHA-1)	
Cert. Fingerprt (SHA-256)	