

\*\*\*\*\*  
\*\*\* Network Configuration Page \*\*\*  
\*\*\*\*\*

1 Product Information

1- 1 Product Name TR7500 series  
1- 2 ROM Version 1.020  
1- 3 Serial Number ABCD00005

2 Network Diagnostics

2- 1 Diagnostic Result Not connected to the network.  
2- 2 Result Codes c-5  
2- 3 Result Code Details <http://canon.com/ijnwt>

3 Wireless LAN

3- 2 Infrastructure Enable  
3- 2- 1 Signal Strength 0[%]  
3- 2- 2 Link Quality 0[%]  
3- 2- 3 Frequency 2.4[GHz]  
  
3- 2- 4 MAC Address 00:99:88:77:66:55  
3- 2- 5 Connection Inactive  
3- 2- 6 SSID This\_Network  
3- 2- 7 Channel  
3- 2- 8 Encryption none  
3- 2- 9 WEP Key Length Inactive  
3- 2-10 Authentication auto  
  
3- 2-11 TCP/IPv4 Enable  
3- 2-12 IP Address  
3- 2-13 Subnet Mask  
3- 2-14 Default Gateway  
  
3- 2-15 TCP/IPv6 Disable  
  
3- 2-16 Link Local Address  
3- 2-17 Link Local Prefix Length  
  
3- 2-18 Stateless Address1  
3- 2-19 Stateless Prefix Length1  
3- 2-20 Stateless Address2  
3- 2-21 Stateless Prefix Length2  
3- 2-22 Stateless Address3  
3- 2-23 Stateless Prefix Length3  
3- 2-24 Stateless Address4  
3- 2-25 Stateless Prefix Length4  
  
3- 2-26 Default Gateway1  
3- 2-27 Default Gateway2  
3- 2-28 Default Gateway3  
3- 2-29 Default Gateway4  
  
3- 2-33 IPsec  
3- 2-34 Security Protocol

3- 3 Wireless Direct	Disable
3- 3- 1 MAC Address	00:AA:BB:CC:DD:EE
3- 3- 2 Connection	
3- 3- 3 SSID	
3- 3- 4 Password	
3- 3- 5 Channel	
3- 3- 6 Encryption	
3- 3- 7 Authentication	
3- 3- 8 TCP/IPv4	
3- 3- 9 IP Address	
3- 3-10 Subnet Mask	
3- 3-11 Default Gateway	
3- 3-12 TCP/IPv6	
3- 3-13 Link Local Address	
3- 3-14 Link Local Prefix Length	
3- 3-15 IPsec	
3- 3-16 Security Protocol	

## 5 Other Settings

5- 1 Printer Name	000000000000
5- 2 Wireless Direct DevName	DIRECT-jiEA-TR7500series
5- 4 WSD Printing	Enable
5- 5 WSD Timeout	15[min]
5- 6 LPD Printing	Enable
5- 7 RAW Printing	Enable
5- 9 Bonjour	Enable
5-10 Bonjour Service Name	Canon TR7500 series
5-11 LLMNR	Enable
5-12 SNMP	Enable
5-13 PictBridge Commun.	Enable
5-14 DNS Server	Auto
5-15 Primary Server	
5-16 Secondary Server	
5-17 Proxy Server	Disable
5-18 Proxy Address	
5-19 Proxy Port	
5-20 Cert. Fingerprt(SHA-1)	
5-21 Cert. Fingerprt(SHA-256)	

## 6 Bluetooth

6- 1 Bluetooth Setting	Enable
6- 2 Bluetooth PIN Code	000000
6- 3 Bluetooth Device Address	00:BB:DD :FF:33:55

6- 4 Peer Device Address  
6- 5 Bluetooth Device Name

TR7500 series