Menu Route Map

```
work Settings
-Select Wired/Wireless LAN
Wireless LAN Settings
      SSID Settings

Select Access Point

Enter Manually

Security Settings
                     -- None
                       -WEP (802.11 Authentication)
                       Open System, Shared key
-WPA/WPA2-PSK
                       (WPA/WPA2 Encryption)

Auto, AES-CCMP
     WPS Push Button Mode
    WPS PIN Code Mode
      Power Save Mode
Off, On
        MAC Address
           -Wireless LAN Status
           -Latest Error Information
          -Channel
           -SSID Settings
            Security Settings
        Power Save Mode
 Direct Connection Settings
    Use Direct Connection
                Direct Connection Only
Wireless LAN/Direct Conn. (Auto Switch)
      Time Until Direct Connection Termination
        0=Off, 1 to 10 to 60 (min.)
      Access Point Mode Settings
           Use Custom SSID 

☐Off, On
           -Use Custom Network Key
                  Off, On
TCP/IP Settings
           -IP Address Settings
                             Off, DHCP, BOOTP, RARP
                       -Auto IP
                         └─Off, On
                  -Manually Acquire
                    IP Address: 0.0.0.0
                        Subnet Mask: 0.0.0.0
                    Gateway Address: 0.0.0.0
                  Check Settings
                    Auto Acquire
                      - IP Address
                       -Subnet Mask
                       -Gateway Address
           -PING Command
            DNS Settings

    DNS Server Settings

                    Primary DNS Server: 0.0.0.0
Secondary DNS Server: 0.0.0.0
                 -DNS Host Name/Domain Name Settings
                       -Host Name
                        Domain Name
                 -DNS Dynamic Update Settings
                    Off, On (DNS Dyn. Updt. Intrvl.)
                              -0 to 24 to 48 (hr.)
            mDNS Settings
             └─Off, On (mDNS Name
            DHCP Option Settings
               Acquire Host Name
                 - DNS Dynamic Update
          -Use IPv6
              └─Off, On, Check Settings
                            Link-Local Address
Prefix Length
                   ss Address Settings
              Off, On, Check Settings
                            Stateless Address
Prefix Length
            Use DHCPv6
             Off, On, Check Settings
Stateful Address
Prefix Length
                -- DNS Host Name/Domain Name Settings
                  (Use IPv4 Host/Domain)
                    └─Off, On
                         Host Name
Domain Name
                  DNS Dynamic Update Settings
                      Off, On
                              Register Stateful Address
                                  Ŭ—<mark>Off</mark>, On
                                Register Stateless Address
                                   └─Off. On
              Off, On (Use IPv4 Name for mDNS)
Off (mDNS Name), On
      LPD Print Settings
      RAW Print Settings
       └─Off. On
      WSD Settings
           -WSD Print Settings
                 Use WSD Print

└─Off, On
               Use WSD Browsing
                        Off, On
           -WSD Scan Settings
              Use WSD Scan
               Use Computer Scan
           -Use Multicast Discovery

☐ Off, On
          Off, On
      Port Number Settings
        LPD 1 to 515 to 65535
             └─1 to 3702 to 65535
            -SNMP
               └─1 to 161 to 65535
      MTU Size
```

```
SNMPv1 Settings
                       nmunity Name 1 Settings
                     └─Off, On
                            MIB Access Permission
                    Community Name 2 Settings
                            Community Name

MIB Access Permission
                   - Dedicated Community Settings
                     └─Off, On
      SNMPv3 Settings
      Coff, On
Acquire Printer Mngt. Info. from Host
        └─Off, On
      cated Port Settings
   Off, On
 Waiting Time for Connection at Startup
   o to 300 (sec.)
  Ethernet Driver Settings
      Auto Detect
Off, On
                -Ethernet Type
                  10BASE-T. 100BASE-TX
IEEE 802.1X Settings
-Initialize Network Setting
```

```
Output Reports

— Consumables Status Report

— Eco Report

— User Data List

— PCL Font List
```

```
Display Settings
          Contrast
L_5 Levels
           nvert Screen Colors

Off, On
          Millimeter/Inch Entry Switch
              -Millimeter, Inch
          Notify to Check Paper Settings
          Gram/Pound Switch
          Message Display Time
               -1 to 2 to 5 (sec.)
          Scrolling Speed
—Slow, Standard, Fast
           Cursor Movement Type

Auto, Manual
          Language
— Chinese (Simplified), Chinese (Traditional),
                English French German Italian Jananese
                Korean, Portuguese, Spanish
           Remote UI Language

— Chinese (Simplified), Chinese (Traditional),
                English, French, German, Italian, Japanese,
                Korean, Portuguese, Spanish
```

```
Settings
Quiet Mode Time
         nd Time
Off, On
Stop time setting to exit quiet mode
   Date/Time Settings
        -Date Format

—YYYY MM/DD, MM/DD/YYYY, DD/MM YYYY
         Fime Format

12 Hour (AM/PM), 24 Hour
        Current Date/Time Settings
         Fime Zone (UTC-12:00) International Date Line West to
              (UTC-05:00) Eastern Time (US & Canada) to (UTC+14:00) Kiritimati Island
         aylight Saving .

Off, On

Start: Month, Day

End: Month, Day
         Daylight Saving Time Settings
   Auto Sleep Time
     1 to 30 (min.)
  Auto Reset Time
     0=Off (Auto Reset is disabled.), 1 to 2 to 9 (min.)
   Function After Auto Reset
        Default Function, Selected Function
Auto Offline Time
    0=Off (The machine remains online.), 1 to 5 to 60 (min.)
```

```
Copy Settings

Change Default Settings

Number of Copies

1 to 999

Density

Original Type

Text/Photo, Photo

2-Sided

Copy Ratio

Custom Ratio, 100% (Direct), 400% (Max), 200%, 129% STMT—LTR, 78% LGL—LTR, 64% LTR—STMT, 50%, 25% (Min)

N on 1

Off, 2 on 1, 4 on 1, ID Card Copy, Select Layout

Collate

Off, 0n

Sharpness

7 Levels

Cortect Density

-4 to 0 to +4

Initialize Default Settings
```

Multi-Purpose Tray

Speed Priority, Print Side Priority

```
Scan Settings
Shortcut Key Settings
Register
Scan -> PC
Off
USB Connection
Custom 2
Network Connection
Color Scan, B&W Scan, Custom 1,
Custom 2
Custom 2
Custom 2
Confirm Destination
Scan -> PC

Printer Settings
```

```
nter Settings

Action When Paper Size Mismatch
    Force Output, Display Error
    Gradation, Error Diffusion
    1 to 999
    Off, On
          17 Levels
Fine Adjust
                 High: 17 Levels

Medium: 17 Levels
         Toner Save
         Off. On
        Special Print Mode
Off, Special Settings 1, Special Settings 2
          esolution 1200 dpi, 600 dpi
         Density Fine Adjustment
        Binding Location

└─Long Edge, Short Edge
    5 to 15 to 300 (sec.)
       Orientation
          Portrait, Landscape
        Font Number
          ____0 to 54
        Point Size
          4.00 to 12.00 to 999.75 (point)
         Pitch _______0.44 to 10.00 to 99.99 (cpi)
         Form Lines
5 to 60 to 128 (lines)
         Character Code

DESKTOP, ISO4, ISO6, ISO11, ISO15, ISO17,
              ISO21, ISO60, ISO69, ISOL1, ISOL2, ISOL5, ISOL6, LEGAL, MATH8, MCTEXT, MSPUBL,
              PC775, PC8, PC850, PC852, PC8DN, PC8TK.
              PC1004, PIFONT, PSMATH, PSTEXT, ROMAN8,
              VNINTI . VNMATH. VNUS. WIN30. WINBALT.
              WINL1, WINL2, WINL5
         Custom Paper
          Off. On
        Unit of Measure
          Millimeters, Inches
          3 to 8 1/2 (inches) or 77 to 216 (mm)
          dimension
__5 to 14 (inches) or 127 to 356 (mm)
         ວ ເປ 14 (incl
Append CR to LF
L ...
            Yes, No
        Enlarge A4 Print Width
              -Text

—Color Tone, Gradation, Resolution
              -Graphics
-Color Tone, Gradation, Resolution
             -Images

___Color Tone, Gradation, Resolution
```

```
stment/Maintenance
     -Displ. Timing for Cartridge Prep. Notif.

1 to 10 to 99 (%)
            Copy
Off, On
           Special Printing Mode U
Off, On
            Special Printing Mode V
               Off. Mode 1, Mode 2, Mode 3
             Special Printing Mode X

Off, Mode 1, Mode 2, Mode 3, Mode 4
             Special Printing Mode Z

Off, Mode 1, Mode 2, Mode 3, Mode 4
            Special Printing Mode B
              Off Mode 1 Mode 2 Mode 3
            Special Printing Mode C
              Off, On
              special Printing Mode D
                —Copy

└─Off, On
                 —Print

└─<mark>Off</mark>, On
                Off, On
            Special Printing Mode J
               pecial Printing
             .

└── Off, On
Clean Fixing Assembly
```

```
Management Settings
 work Settings

→Network Settings
   System Manager Name
  Device Name
    ocation
   Use TLS
    IPv4 Address Filter
    └─Off, On
    IPv6 Address Filter
    IAC Address Filter
    United States (US), Canada (CA), Brazil (BR),
  Mexico (MX), Other
  Use Remote UI
    emote UI Access Security Settings
 Off, On
    Consmbls. Info (RUI/Toner Status)
   Displ. Consumables Purchase Button (RUI)
     └─Off, On
    oner Status Settings

Off, On (Displ. Purchase Button)

Off, On
      Cloud Print Settings
    nable Google Cloud Print
     oogle Cloud Print Registration Status
     etwork
UFRII LT, UFRII LT (V4), PCL6
       -UFRII LT, UFRII LT (V4), PCL6
 Via PC, Via Internet, Version Information
   lize Eco Report Counter
   Preferences
    mer Settings
     ommon Settings
   Copy Settings
   Printer Settings
    djustment/Maintenance
    System Management Settings
      -Network Settings
       System Manager Information Settings
        -Device Information Settings
        Security/Remote UI Settings
       -Auto Online for Remote Scan
       Use as USB Device
        -Enable Product Extended Survey Program
        Displ. Consmbls. Info (RUI/Toner Status)
        -Google Cloud Print Settings
        -PDL Selection (Plug and Play)
    Initialize All
```