```
Direct Connection
      Wireless LAN Settings
             SSID Settings
                  Select Access Point
                 -Enter Manually
                    Security Settings
                            -None
                                          Select WEP Key . 1
                                              WEP Key 1 to 4
                                         -Edit WEP Key
-WEP Key 1 to 4
                                        ared kev
                                          Select WEP Key . 1
WEP Key 1 to 4
                                         Edit WEP Key
WEP Key 1 to 4
                              WPA/WPA2-PSK
                                  Auto, AES-CCMP
            WPS Push Button Mode
            WPS PIN Code Mode
            Power Save Mode
             └─Off, On
            Wireless LAN Information
               MAC Address
                  -Wireless LAN Status
                 -Latest Error Information
                 -SSID Settings
                  -Security Settings
                 -Power Save Mode
      Direct Connection Settings
            Use Direct Connection
                    Direct Connection Only
Wireless LAN/Direct Conn. (Auto Switch)
            Time Until Direct Connection Termination
              ☐0 (Do not terminate session automatically),
                 1 to 10 to 60 (min.)
                cess Point Mode Settings
                 -Use Custom SSID
                    ⊢off
⊢on
└─SSID
                  -Use Custom Network Key
                    Off
On
                             -Network key
      Easy Connection via PC
      TCP/IP Settings
            IPv4 Settings
                 -IP Address Settings
                        Auto Acquire
                          Select Protocol
                                Off, DHCP, BOOTP, RARP
                             -Auto IP
                                └─Off, On
                        Manually Acquire
                           IP Address: 0.0.0.0
                             -Subnet Mask: 0.0.0.0
                          Gateway Address: 0.0.0.0
                         Check Settings
                            -Auto Acquire
                             - IP Address
                          Subnet Mask
Gateway Address
                  PING Command
                 -DNS Settings
                        -DNS Server Settings
                        Primary DNS Server: 0.0.0.0

Secondary DNS Server: 0.0.0.0

DNS Host Name/Domain Name Settings
                         Host Name
Domain Name
                        DNS Dynamic Update Settings
                        On DNS Dyn. Updt. Intrvl.
                  -DHCP Option Settings
                       —Acquire Host Name

└─Off, On
                       -DNS Dynamic Update
                            Off, On
            TPv6 Settings
                Use IPv6
                        Off
                        -Check Settings
                         Link-Local Address
Prefix Length
                  -Stateless Address Settings
                    -Off
                         Stateless Address
Prefix Length
                  Use DHCPv6
                       -Off
                        -On
                        -Check Settings
                          Stateful Address
Prefix Length
                  -DNS Settings
                       -DNS Host Name/Domain Name Settings
                                Host Name
Domain Name
                    DNS Dynamic Update Settings
                          Off
On
                                    Register Manual Address
                                    Register Stateful Address
                                    Register Stateless Address
                                   -DNS Dynamic Update Interval
                                        -0 to 24 to 48 (hr.)
```

```
Menu Route Map
          LPD Print Settings
           RAW Print Setting
            └─Off, On
           WSD Settings
               -WSD Print Settings
                    −Use WSD Print

└─Off, On
                    -Use WSD Browsing
                      └─Off, On
               -Use Multicast Discovery
                 └─Off, On
          Use HTTP
            └─Off, On
           └─1 to 9100 to 65535
                WSD Multicast Discovery

—1 to 3702 to 65535
               -HTTP 1 to 80 to 65535
                 └─1 to 161 to 65535
          MTU Size
              —1300, 1400, 1500
     SNMP Settings
          SNMPv1 Settings
             SNMPv1 Settings
                Community Name 1 Settings
                          Community Name
                         -MIB Access Permission
                            Read/Write, Read Only
                Community Name 2 Settings
                 Off
On
                         -Community Name
                      MIB Access Permission
Read/Write, Read Only
                Dedicated Community Settings
                 Off
On
                      Read/Write, Read Only
          SNMPv3 Settings
           └─Off, On
           Acquire Printer Mngt. Info. from Host
           Off, On
     Dedicated Port Settings
  Settings marked with an asterisk (*) may 
you are using or other setting items.
Outnut Reports
                les Status Report
     Eco Report
   — User Data List
  Display Settings
          Contrast
           Five Levels
           nvert Screen Colors
           Millimeter/Inch Entry Switch
            Millimeter, Inch
           Gram/Pound Switch
Gram, Pound
           Notify to Check Paper Settings
           └─Off, On
           Message Display Time

1 to 2 to 5 (sec.)
           Scrolling Speed
           Language
            Chinese (Simplified), Chinese (Traditional),
               English, French, German, Italian, Japanese,
               Korean, Portuguese, Spanish
```

```
emote UI Language
—Chinese (Simplified), Chinese (Traditional),
    English, French, German, Italian, Japanese,
    Korean, Portuguese, Spanish
```

```
imer Settings
— Date/Time Settings
          └─YYYY MM/DD, MM/DD/YYYY, DD/MM YYYY
          Time Format
          12 Hour (AM/PM), 24 Hour
          Current Date/Time Settings
         Time Zone
          (UTC-12:00) International Date Line West to
              (UTC-05:00) Eastern Time (US & Canada) to
               (UTC+14:00) Kiritimati Island
         Daylight Saving Time Settings
          Off
On
                Start: Month, Week, Day
End: Month, Week, Day
   Auto Sleep Time
     └─_1 to 30 (min.)
  Auto Reset Time
         0 (Auto Reset is disabled.), 1 to 2 to 9 (min.)
```

```
inter Settings
—<mark>Action When </mark>Paper Size Mismatch
    Force Output,
        ge Quality Settings for Mobile Print
         Halftone
Gradation, Error Diffusion
          riority
Standard, Speed Priority, Image Quality Priority
     Toner Save
```

```
Custom^*, LTR^*, LGL^*, STMT^*, EXEC^*, FOOLSCAP^*,
   OFICIO*, No. 10 (COM10)*, Monarch*,
Government-LTR*, Government-LGL*, India-LGL*,
AUS-FOOLSCAP*,Brazil-OFICIO*, Mexico-OFICIO*, F4A*,
    3x5inch*, A4*, A5*, B5*, DL*, ISO-C5*, <Other Sizes>
        —Plain (19 lb Bond-23 lb Bond)*,
          Plain L (17 lb Bond-18 lb Bond)*,
          Plain L2 (16 lb Bond)*,
          Recycled (19 lb Bond-23 lb Bond)*,
          Heavy 1 (24 lb Bond-32 lb Bond)*
          Heavy 2 (33 lb Bond-60 lb Cover)*,
Heavy 3 (33 lb Bond-60 lb Cover)*, Labels*,
          Bond 1 (16 lb Bond-27 lb Bond)*
          Bond 2 (28 lb Bond-60 lb Cover)*, Envelope*,
          Envelope H*
Custom, LTR, LGL, STMT, EXEC, FOOLSCAP, OFICIO, No. 10 (COM10), Monarch, Government-LTR,
   Government-LGL, India-LGL, AUS-FOOLSCAP
    Brazil-OFICIO, Mexico-OFICIO, F4A, 3x5inch, A4, A5,
   B5, DL, ISO-C5
```

```
Displ. Timing for Cartridge Prep. Notif.
         oner Cartridge

└─1 to 20 to 99 (%)
       Drum Cartridge
         └─1 to 10 to 99 (%)
       al Processing
       Special Printing Mode U
        Off, On
Special Printing Mode A
Off, Mode 1, Mode 2
        Special Printing Mode G
           Off, On
       Special Printing Mode Q
        Special Printing Mode R
         Off, On
        Special Printing Mode T
        Special Printing Mode L
         └─Off, On
        Select Line Width
         LAuto, Thin, Slightly Thin, Slightly Thick, Thick
  Clean Fixing Assembly
```

```
System Management Settings

Network Settings

Network Settings
           System Manager PIN
          System Manager Name
           Location
             se TLS
              └─Off. On
             Pv4 Address Filter
Inbound Filter
                   Off, On
             Pv6 Address Filter
             Inbound Filter
             United States (US), Canada (CA), Brazil (BR),
           Mexico (MX), Other
            te UI Setti
             └─Off, On
              mote UI Access Security Settings
             Off
On
                   Remote UI Access PIN
        se as USB Dev
        Off, On
                   mbls. Info (RUI/Toner Status)
             ispl. Consumables Purchase Button (RUI)

Off, On
             oner Status Settings
             Off
On
                   Displ. Purchase Button
Off, On
              able Google Cloud Print
              └─Off, On
            Google Cloud Print Registration Status
                 tion (Plug and Play)
                UFRII LT, UFRII LT (V4)
             UFRII LT, UFRII LT (V4)
        pdate Firmware

Via PC, Via Internet, Version Information
            Preferences
             imer Settinas
              rinter Settings
            Adjustment/Maintenance
             ystem Management Settings
                 - Network Settings
                 -System Manager Information Settings
                 -Device Information Settings
                 -Security/Remote III Settings
                 -Display Job Log

    Use as USB Device

                 -Enable Product Extended Survey Program

    Displ. Consmbls. Info (RUI/Toner Status)

                -Google Cloud Print Settings
                 -PDL Selection (Plug and Play)
                 -Initialize All
           alize All Data/Settings
```