
*** Network Configuration Page ***

1 Product Information
1- 1 Product Name TS9100 series
1- 2 ROM Version 1.100
1- 3 Serial Number AFDB34623

2 Network Diagnostics
2- 1 Diagnostic Result There is no problem.
2- 2 Result Codes c-0
2- 3 Result Code Details <http://canon.com/ijnwt>

3 Wireless LAN Enable
3- 2 Infrastructure Enable
3- 2- 1 Signal Strength 73[%]
3- 2- 2 Link Quality 72[%]
3- 2- 3 Frequency 2.4 [GHz]

3- 2- 4 MAC Address 00:00:00:00:11:22
3- 2- 5 Connection Active
3- 2- 6 SSID ABCD_EFG
3- 2- 7 Channel 11
3- 2- 8 Encryption AES
3- 2- 9 WEP Key Length Inactive
3- 2-10 Authentication WPA2-PSK

3- 2-11 TCP/IPv4 Enable
3- 2-12 IP Address 172.21.29.129
3- 2-13 Subnet Mask 255.255.255.0
3- 2-14 Default Gateway 172.21.29.1

3- 2-15 TCP/IPv6 Enable

3- 2-16 Link Local Address feaa::2bb:c3ff:febc:5f5e
3- 2-17 Link Local Prefix Length 64

3- 2-18 Stateless Address1
3- 2-19 Stateless Prefix Length1
3- 2-20 Stateless Address2
3- 2-21 Stateless Prefix Length2
3- 2-22 Stateless Address3
3- 2-23 Stateless Prefix Length3
3- 2-24 Stateless Address4
3- 2-25 Stateless Prefix Length4

3- 2-26 Default Gateway1
3- 2-27 Default Gateway2
3- 2-28 Default Gateway3
3- 2-29 Default Gateway4

3- 2-33 IPsec Inactive
3- 2-34 Security Protocol

3- 2-35 Wireless LAN DRX	Enable
3- 3 Wireless Direct	Disable
3- 3- 1 MAC Address	02:BB:C1:BC:5F:8E
3- 3- 2 Connection	
3- 3- 3 SSID	
3- 3- 4 Password	
3- 3- 5 Channel	
3- 3- 6 Encryption	
3- 3- 7 Authentication	
3- 3- 8 TCP/IPv4	
3- 3- 9 IP Address	
3- 3-10 Subnet Mask	
3- 3-11 Default Gateway	
3- 3-12 TCP/IPv6	
3- 3-13 Link Local Address	
3- 3-14 Link Local Prefix Length	
3- 3-15 IPsec	
3- 3-16 Security Protocol	
3- 3-17 Wireless LAN DRX	
4 Wired LAN	Disable
4- 1 MAC Address	00:BB:C1:6E:F5:5B
4- 2 Connection	
4- 3 TCP/IPv4	
4- 4 IP Address	
4- 5 Subnet Mask	
4- 6 Default Gateway	
4- 7 TCP/IPv6	
4- 8 Link Local Address	
4- 9 Link Local Prefix Length	
4-10 Stateless Address1	
4-11 Stateless Prefix Length1	
4-12 Stateless Address2	
4-13 Stateless Prefix Length2	
4-14 Stateless Address3	
4-15 Stateless Prefix Length3	
4-16 Stateless Address4	
4-17 Stateless Prefix Length4	
4-18 Default Gateway1	
4-19 Default Gateway2	
4-20 Default Gateway3	
4-21 Default Gateway4	

4-25 IPsec
4-26 Security Protocol

4-27 Wired LAN DRX

5 Other Settings

5- 1 Printer Name	BC0000000000
5- 2 Wireless Direct DevName	DIRECT-gA8E-TS9100series
5- 4 WSD Printing	Enable
5- 5 WSD Timeout	15[min]
5- 6 LPD Printing	Enable
5- 7 RAW Printing	Enable
5- 9 Bonjour	Enable
5-10 Bonjour Service Name	Canon TS9100 series
5-11 LLMNR	Enable
5-12 SNMP	Enable
5-13 PictBridge Commun.	Enable
5-14 DNS Server	Auto
5-15 Primary Server	8.8.8.8
5-16 Secondary Server	8.8.4.4
5-17 Proxy Server	Disable
5-18 Proxy Address	
5-19 Proxy Port	
5-20 Cert. Fingerprt(SHA-1)	ffffff49 6009964c 8f00a5e5 753d17fb
5-21 Cert. Fingerprt(SHA-256)	5e0000ea 0a7000a2 d5000a7b bd0009d6 c60000ba 20005c8e 8000048b 1400002f 5b000168

6 Bluetooth

6- 1 Bluetooth Setting	Disable
6- 2 Bluetooth PIN Code	004623
6- 3 Bluetooth Device Address	00:BB:C1:30:0D:A0
6- 4 Peer Device Address	
6- 4- 1 Peer Device Address1	04:C2:3E:0B:55:3B
6- 5 Bluetooth Device Name	TS9100 series