
*** Network Configuration Page ***

1 Product Information

1- 1 Product Name TS700 series
1- 2 ROM Version 1.000
1- 3 Serial Number ABCD01234

2 Network Diagnostics

2- 1 Diagnostic Result There is a problem in the settings/environment.
2- 2 Result Codes c-0,c-9
2- 3 Result Code Details <http://canon.com/ijnwt>

3 Wireless LAN

Enable

3- 2 Infrastructure

Enable

3- 2- 1 Signal Strength 75[%]
3- 2- 2 Link Quality 58[%]
3- 2- 3 Frequency 2.4 [GHz]

3- 2- 4 MAC Address AA:AA:AA:AA:AA:AA
3- 2- 5 Connection Active
3- 2- 6 SSID My Network
3- 2- 7 Channel 6
3- 2- 8 Encryption AES
3- 2- 9 WEP Key Length Inactive
3- 2-10 Authentication WPA2-PSK

3- 2-11 TCP/IPv4 Enable
3- 2-12 IP Address 192.168.1.150
3- 2-13 Subnet Mask 255.255.255.0
3- 2-14 Default Gateway 192.168.1.1

3- 2-15 TCP/IPv6 Enable

3- 2-16 Link Local Address ffff::ffff:ffff:ffff:ffff
3- 2-17 Link Local Prefix Length 64

3- 2-18 Stateless Address1
3- 2-19 Stateless Prefix Length1
3- 2-20 Stateless Address2
3- 2-21 Stateless Prefix Length2
3- 2-22 Stateless Address3
3- 2-23 Stateless Prefix Length3
3- 2-24 Stateless Address4
3- 2-25 Stateless Prefix Length4

3- 2-26 Default Gateway1
3- 2-27 Default Gateway2
3- 2-28 Default Gateway3
3- 2-29 Default Gateway4

3- 2-33 IPsec Inactive

3- 2-34 Security Protocol

- 3- 3 Wireless Direct Disable
- 3- 3- 1 MAC Address 11:11:11:11:11:11
- 3- 3- 2 Connection
- 3- 3- 3 SSID
- 3- 3- 4 Password
- 3- 3- 5 Channel
- 3- 3- 6 Encryption
- 3- 3- 7 Authentication

- 3- 3- 8 TCP/IPv4
- 3- 3- 9 IP Address
- 3- 3-10 Subnet Mask
- 3- 3-11 Default Gateway

- 3- 3-12 TCP/IPv6

- 3- 3-13 Link Local Address
- 3- 3-14 Link Local Prefix Length

- 3- 3-15 IPsec
- 3- 3-16 Security Protocol

4 Wired LAN

Disable
22:22:22:22:22:22

- 4- 1 MAC Address
- 4- 2 Connection
- 4- 3 TCP/IPv4
- 4- 4 IP Address
- 4- 5 Subnet Mask
- 4- 6 Default Gateway

- 4- 7 TCP/IPv6

- 4- 8 Link Local Address
- 4- 9 Link Local Prefix Length

- 4-10 Stateless Address1
- 4-11 Stateless Prefix Length1
- 4-12 Stateless Address2
- 4-13 Stateless Prefix Length2
- 4-14 Stateless Address3
- 4-15 Stateless Prefix Length3
- 4-16 Stateless Address4
- 4-17 Stateless Prefix Length4

- 4-18 Default Gateway1
- 4-19 Default Gateway2
- 4-20 Default Gateway3
- 4-21 Default Gateway4

- 4-25 IPsec
- 4-26 Security Protocol

- 4-27 Wired LAN DRX

5 Other Settings

5- 1 Printer Name	000000000000
5- 2 Wireless Direct DevName	DIRECT-kK1B-TS700series
5- 4 WSD Printing	Enable
5- 5 WSD Timeout	15[min]
5- 6 LPD Printing	Enable
5- 7 RAW Printing	Enable
5- 9 Bonjour	Enable
5-10 Bonjour Service Name	Canon TS700 series
5-11 LLMNR	Enable
5-12 SNMP	Enable
5-13 PictBridge Commun.	Enable
5-14 DNS Server	Auto
5-15 Primary Server	11.22.33.44
5-16 Secondary Server	11.22.33.44
5-17 Proxy Server	Disable
5-18 Proxy Address	
5-19 Proxy Port	
5-20 Cert. Fingerprt(SHA-1)	abababab abababab abababab abababab abababab
5-21 Cert. Fingerprt(SHA-256)	abababab abababab abababab abababab abababab abababab abababab abababab

6 Bluetooth

6- 1 Bluetooth Setting	Enable
6- 3 Bluetooth Device Address	00:11:22:33:44:55
6- 5 Bluetooth Device Name	TS700 series