

\*\*\*\*\*  
\*\*\* Network Configuration Page \*\*\*  
\*\*\*\*\*

1 Product Information

1- 1 Product Name TS300 series  
1- 2 ROM Version 1.000  
1- 3 Serial Number AAAA00000

2 Network Diagnostics

2- 1 Diagnostic Result Not connected to the network.  
2- 2 Result Codes c-5  
2- 3 Result Code Details <http://canon.com/ijnwt>

3 Wireless LAN

3- 1 WPS PIN CODE Enable  
12345678

3- 2 Infrastructure

3- 2- 1 Signal Strength Enable  
0[%]  
3- 2- 2 Link Quality 0[%]  
3- 2- 3 Frequency 2.4 [GHz]  
3- 2- 4 MAC Address FF:FF:FF:FF:FF:CC  
3- 2- 5 Connection Inactive  
3- 2- 6 SSID My\_Network  
3- 2- 7 Channel  
3- 2- 8 Encryption AES  
3- 2- 9 WEP Key Length Inactive  
3- 2-10 Authentication WPA2-PSK

3- 2-11 TCP/IPv4 Enable  
3- 2-12 IP Address  
3- 2-13 Subnet Mask  
3- 2-14 Default Gateway

3- 2-15 TCP/IPv6 Enable

3- 2-16 Link Local Address  
3- 2-17 Link Local Prefix Length

3- 2-18 Stateless Address1  
3- 2-19 Stateless Prefix Length1  
3- 2-20 Stateless Address2  
3- 2-21 Stateless Prefix Length2  
3- 2-22 Stateless Address3  
3- 2-23 Stateless Prefix Length3  
3- 2-24 Stateless Address4  
3- 2-25 Stateless Prefix Length4

3- 2-26 Default Gateway1  
3- 2-27 Default Gateway2  
3- 2-28 Default Gateway3  
3- 2-29 Default Gateway4

3- 2-33 IPsec Inactive  
3- 2-34 Security Protocol

3- 3 Access Point Mode Enable  
3- 3- 1 MAC Address FF:FF:FF:FF:FF:FF  
3- 3- 2 Connection Active  
3- 3- 3 SSID 9A7FCC-TS300series  
3- 3- 4 Password AAAA00AAA  
3- 3- 5 Channel 1  
3- 3- 6 Encryption AES  
3- 3- 7 Authentication WPA2-PSK

3- 3- 8 TCP/IPv4 Enable  
3- 3- 9 IP Address 192.168.1.150  
3- 3-10 Subnet Mask 255.255.255.0  
3- 3-11 Default Gateway 192.168.1.1

3- 3-12 TCP/IPv6 Enable

3- 3-13 Link Local Address ffff::ffff:ffff:ffff:ffff  
3- 3-14 Link Local Prefix Length 64

3- 3-15 IPsec Inactive  
3- 3-16 Security Protocol

## 5 Other Settings

5- 1 Printer Name 000000000000  
5- 4 WSD Printing Enable  
5- 5 WSD Timeout 15[min]

5- 6 LPD Printing Enable  
5- 7 RAW Printing Enable

5- 9 Bonjour Enable  
5-10 Bonjour Service Name Canon TS300 series

5-11 LLMNR Enable  
5-12 SNMP Enable

5-13 PictBridge Commun. Enable

5-14 DNS Server Auto

5-15 Primary Server  
5-16 Secondary Server  
5-17 Proxy Server Disable

5-18 Proxy Address  
5-19 Proxy Port

5-20 Cert. Fingerprt(SHA-1) 00000000 00000000 00000000 00000000 00000000  
5-21 Cert. Fingerprt(SHA-256) 00000000 00000000 00000000 00000000 00000000  
00000000 00000000 00000000

## 6 Bluetooth

6- 1 Bluetooth Setting Enable  
6- 2 Bluetooth PIN Code 000000

6- 3 Bluetooth Device Address 00:00:00:00:00:00  
6- 4 Peer Device Address  
6- 5 Bluetooth Device Name TS300 series

\*\*\*\*\*  
\* Bluetooth 000000 \*  
\*\*\*\*\*