
*** Network Configuration Page ***

1 Product Information

1- 1 Product Name TR8600 series
1- 2 ROM Version 1.010
1- 3 Serial Number ABCD12345

2 Network Diagnostics

2- 1 Diagnostic Result Not connected to the network.
2- 2 Result Codes C-3
2- 3 Result Code Details <http://canon.com/ijnwt>

3 Wireless LAN

Enable

3- 2 Infrastructure

Enable

3- 2- 1 Signal Strength 72[%]
3- 2- 2 Link Quality 76[%]
3- 2- 3 Frequency 2.4 [GHz]

3- 2- 4 MAC Address AA:BB:CC:DD:EE:FF
3- 2- 5 Connection Active
3- 2- 6 SSID My_Network
3- 2- 7 Channel 11
3- 2- 8 Encryption AES
3- 2- 9 WEP Key Length Inactive
3- 2-10 Authentication WPA2-PSK

3- 2-11 TCP/IPv4 Enable
3- 2-12 IP Address
3- 2-13 Subnet Mask
3- 2-14 Default Gateway

3- 2-15 TCP/IPv6 Enable

3- 2-16 Link Local Address
3- 2-17 Link Local Prefix Length

3- 2-18 Stateless Address1
3- 2-19 Stateless Prefix Length1
3- 2-20 Stateless Address2
3- 2-21 Stateless Prefix Length2
3- 2-22 Stateless Address3
3- 2-23 Stateless Prefix Length3
3- 2-24 Stateless Address4
3- 2-25 Stateless Prefix Length4

3- 2-26 Default Gateway1
3- 2-27 Default Gateway2
3- 2-28 Default Gateway3
3- 2-29 Default Gateway4

3- 2-33 IPsec Inactive

3- 2-34 Security Protocol

3- 3 Wireless Direct	Disable
3- 3- 1 MAC Address	AA:BB:CC:DD:EE:FF
3- 3- 2 Connection	
3- 3- 3 SSID	
3- 3- 4 Password	
3- 3- 5 Channel	
3- 3- 6 Encryption	
3- 3- 7 Authentication	
3- 3- 8 TCP/IPv4	
3- 3- 9 IP Address	
3- 3-10 Subnet Mask	
3- 3-11 Default Gateway	
3- 3-12 TCP/IPv6	
3- 3-13 Link Local Address	
3- 3-14 Link Local Prefix Length	
3- 3-15 IPsec	
3- 3-16 Security Protocol	

4 Wired LAN

4- 1 MAC Address	Disable
4- 2 Connection	AA:BB:CC:DD:EE:FF
4- 3 TCP/IPv4	
4- 4 IP Address	
4- 5 Subnet Mask	
4- 6 Default Gateway	
4- 7 TCP/IPv6	
4- 8 Link Local Address	
4- 9 Link Local Prefix Length	
4-10 Stateless Address1	
4-11 Stateless Prefix Length1	
4-12 Stateless Address2	
4-13 Stateless Prefix Length2	
4-14 Stateless Address3	
4-15 Stateless Prefix Length3	
4-16 Stateless Address4	
4-17 Stateless Prefix Length4	
4-18 Default Gateway1	
4-19 Default Gateway2	
4-20 Default Gateway3	
4-21 Default Gateway4	
4-25 IPsec	
4-26 Security Protocol	
4-27 Wired LAN DRX	

5 Other Settings

5- 1 Printer Name	000000000000
5- 2 Wireless Direct DevName	DIRECT-ABCD-TR8600series
5- 4 WSD Printing	Enable
5- 5 WSD Timeout	15[min]
5- 6 LPD Printing	Enable
5- 7 RAW Printing	Enable
5- 9 Bonjour	Enable
5-10 Bonjour Service Name	Canon TR8600 series
5-11 LLMNR	Enable
5-12 SNMP	Enable
5-13 PictBridge Commun.	Enable
5-14 DNS Server	Auto
5-15 Primary Server	
5-16 Secondary Server	
5-17 Proxy Server	Disable
5-18 Proxy Address	
5-19 Proxy Port	
5-20 Cert. Fingerprt(SHA-1)	88888888 88888888 88888888 88888888 88888888
5-21 Cert. Fingerprt(SHA-256)	88888888 88888888 88888888 88888888 88888888 88888888 88888888 88888888

6 Bluetooth

6- 1 Bluetooth Setting	Enable
6- 3 Bluetooth Device Address	AA:BB:CC:DD:EE:F
6- 5 Bluetooth Device Name	TR8600 series

7 Web Services

7- 1 Unsent Usage Logs	0
7- 2 Usage Log Last Sent	
7- 3 Web Service Status	Registered
7- 4 Log Transmission Status	Active