

\*\*\*\*\*  
\*\*\* Network Configuration Page \*\*\*  
\*\*\*\*\*

1 Product Information

1- 1 Product Name PRO-200 series  
1- 2 ROM Version 1.020  
1- 3 Serial Number ABCD12345

2 Network Diagnostics

2- 1 Diagnostic Result Not connected to the network.  
2- 2 Result Codes c-1  
2- 3 Result Code Details <http://canon.com/ijnwt>

3 Wireless LAN

Disable

3- 2 Infrastructure

Disable

3- 2- 1 Signal Strength  
3- 2- 2 Link Quality  
3- 2- 3 Frequency

3- 2- 4 MAC Address 11:22:33:44:55:66

3- 2- 5 Connection

3- 2- 6 SSID

3- 2- 7 Channel

3- 2- 8 Encryption

3- 2- 9 WEP Key Length

3- 2-10 Authentication

3- 2-11 TCP/IPv4

3- 2-12 IP Address

3- 2-13 Subnet Mask

3- 2-14 Default Gateway

3- 2-15 TCP/IPv6

3- 2-16 Link Local Address

3- 2-17 Link Local Prefix Length

3- 2-18 Stateless Address1

3- 2-19 Stateless Prefix Length1

3- 2-20 Stateless Address2

3- 2-21 Stateless Prefix Length2

3- 2-22 Stateless Address3

3- 2-23 Stateless Prefix Length3

3- 2-24 Stateless Address4

3- 2-25 Stateless Prefix Length4

3- 2-26 Default Gateway1

3- 2-27 Default Gateway2

3- 2-28 Default Gateway3

3- 2-29 Default Gateway4

3- 2-30 Manual Setting

3- 2-31 IP Address  
3- 2-32 Subnet Prefix Length

3- 2-33 IPsec  
3- 2-34 Security Protocol

3- 2-35 Wireless LAN DRX

3- 3 Wireless Direct Disable  
3- 3- 1 MAC Address 11:22:33:44:55:66  
3- 3- 2 Connection  
3- 3- 3 SSID  
3- 3- 4 Password  
3- 3- 5 Channel  
3- 3- 6 Encryption  
3- 3- 7 Authentication  
  
3- 3- 8 TCP/IPv4  
3- 3- 9 IP Address  
3- 3-10 Subnet Mask  
3- 3-11 Default Gateway  
  
3- 3-12 TCP/IPv6  
  
3- 3-13 Link Local Address  
3- 3-14 Link Local Prefix Length  
  
3- 3-15 IPsec  
3- 3-16 Security Protocol  
  
3- 3-17 Wireless LAN DRX

4 Wired LAN Disable  
4- 1 MAC Address 11:22:33:44:55:66  
4- 2 Connection  
4- 3 TCP/IPv4  
4- 4 IP Address  
4- 5 Subnet Mask  
4- 6 Default Gateway  
  
4- 7 TCP/IPv6  
  
4- 8 Link Local Address  
4- 9 Link Local Prefix Length  
  
4-10 Stateless Address1  
4-11 Stateless Prefix Length1  
4-12 Stateless Address2  
4-13 Stateless Prefix Length2  
4-14 Stateless Address3  
4-15 Stateless Prefix Length3  
4-16 Stateless Address4  
4-17 Stateless Prefix Length4  
  
4-18 Default Gateway1

4-19 Default Gateway2

4-20 Default Gateway3

4-21 Default Gateway4

4-22 Manual Setting

4-23 IP Address

4-24 Subnet Prefix Length

4-25 IPsec

4-26 Security Protocol

4-27 Wired LAN DRX

## 5 Other Settings

5- 1 Printer Name

000000000000

5- 2 Wireless Direct DevName

DIRECT-ABCD-PRO-200series

5- 4 WSD Printing

Enable

5- 5 WSD Timeout

15[min]

5- 6 LPD Printing

Enable

5- 7 RAW Printing

Enable

5- 9 Bonjour

Enable

5-10 Bonjour Service Name

Canon PRO-200 series

5-11 LLMNR

Enable

5-12 SNMP

Enable

5-13 PictBridge Commun.

Enable

5-14 DNS Server

5-15 Primary Server

5-16 Secondary Server

5-17 Proxy Server

5-18 Proxy Address

5-19 Proxy Port

5-20 Cert. Fingerprt(SHA-1)

88888888 88888888 88888888 88888888 88888888

5-21 Cert. Fingerprt(SHA-256)

88888888 88888888 88888888 88888888 88888888  
88888888 88888888 88888888

## 7 Web Services

7- 1 Unsent Usage Logs

0

7- 2 Usage Log Last Sent

7- 3 Web Service Status

Registered

7- 4 Log Transmission Status

Error