
*** Network Configuration Page ***

1 Product Information

1- 1 Product Name GX6000 series
1- 2 ROM Version 2.010
1- 3 Serial Number ABCD12345
1- 4 Default Password AaBbCcDd

2 Network Diagnostics

2- 1 Diagnostic Result Not connected to the network.
2- 2 Result Codes C-3,C-9
2- 3 Result Code Details <http://canon.com/ijnwt>

3 Wireless LAN

Enable

3- 2 Infrastructure

Enable

3- 2- 1 Signal Strength 85 [%]
3- 2- 2 Link Quality 90 [%]
3- 2- 3 Frequency 5 [GHz]

3- 2- 4 MAC Address AA:BB:CC:DD:EE:FF
3- 2- 5 Connection Active
3- 2- 6 SSID My Network
3- 2- 7 Channel 40
3- 2- 8 Encryption AES
3- 2- 9 WEP Key Length Inactive
3- 2-10 Authentication WPA2-PSK

3- 2-11 TCP/IPv4 Enable

3- 2-12 IP Address

3- 2-13 Subnet Mask

3- 2-14 Default Gateway

3- 2-15 TCP/IPv6 Disable

3- 2-16 Link Local Address

3- 2-17 Link Local Prefix Length

3- 2-18 Stateless Address1

3- 2-19 Stateless Prefix Length1

3- 2-20 Stateless Address2

3- 2-21 Stateless Prefix Length2

3- 2-22 Stateless Address3

3- 2-23 Stateless Prefix Length3

3- 2-24 Stateless Address4

3- 2-25 Stateless Prefix Length4

3- 2-26 Default Gateway1

3- 2-27 Default Gateway2

3- 2-28 Default Gateway3

3- 2-29 Default Gateway4

3- 2-33 IPsec
3- 2-34 Security Protocol

3- 2-35 Wireless LAN DRX Disable

3- 3 Wireless Direct Disable
3- 3- 1 MAC Address AA:BB:CC:DD:EE:FF

3- 3- 2 Connection
3- 3- 3 SSID
3- 3- 4 Password
3- 3- 5 Channel
3- 3- 6 Encryption
3- 3- 7 Authentication

3- 3- 8 TCP/IPv4
3- 3- 9 IP Address
3- 3-10 Subnet Mask
3- 3-11 Default Gateway

3- 3-12 TCP/IPv6

3- 3-13 Link Local Address
3- 3-14 Link Local Prefix Length

3- 3-15 IPsec
3- 3-16 Security Protocol

3- 3-17 Wireless LAN DRX

4 Wired LAN Disable
4- 1 MAC Address AA:BB:CC:DD:EE:FF

4- 2 Connection
4- 3 TCP/IPv4
4- 4 IP Address
4- 5 Subnet Mask
4- 6 Default Gateway

4- 7 TCP/IPv6

4- 8 Link Local Address
4- 9 Link Local Prefix Length

4-10 Stateless Address1
4-11 Stateless Prefix Length1
4-12 Stateless Address2
4-13 Stateless Prefix Length2
4-14 Stateless Address3
4-15 Stateless Prefix Length3
4-16 Stateless Address4
4-17 Stateless Prefix Length4

4-18 Default Gateway1
4-19 Default Gateway2
4-20 Default Gateway3
4-21 Default Gateway4

4-25 IPsec
4-26 Security Protocol

4-27 Wired LAN DRX

5 Other Settings

5- 1 Printer Name	000000000000
5- 2 Wireless Direct DevName	DIRECT-KS7E-GX6000series
5- 4 WSD Printing	Disable
5- 5 WSD Timeout	15[min]
5- 6 LPD Printing	Enable
5- 7 RAW Printing	Enable
5- 9 Bonjour	Enable
5-10 Bonjour Service Name	Canon GX6000 series
5-11 LLMNR	Enable
5-12 SNMP	Enable
5-14 DNS Server	Auto
5-15 Primary Server	
5-16 Secondary Server	
5-17 Proxy Server	Disable
5-18 Proxy Address	
5-19 Proxy Port	
5-20 Cert. Fingerprt(SHA-1)	00000000 00000000 00000000 00000000 00000000
5-21 Cert. Fingerprt(SHA-256)	00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000